

IMAGE PROCESSING APPARATUS, IMAGE PROCESSING  
SYSTEM, IMAGE PROCESSING METHOD, AND STORAGE MEDIUM

BACKGROUND OF THE INVENTION

5 Field of the Invention

The invention relates to an image processing  
apparatus, an image processing system, and an image  
processing method which are used in, for example, an  
apparatus or system for managing a number of images and  
10 displaying a list of reduced images (thumbnail images)  
of those images and to a storage medium in which  
processing steps for embodying them have been stored in  
a computer-readable state.

Related Background Art

15 In recent years, for example, there have been used  
many software (hereinafter, referred to as "image  
management list display software") for fetching a  
number of images obtained by an image input device such  
as scanner, digital camera, or the like into a personal  
20 computer (hereinafter, simply referred to as "PC") and  
displaying a list of them.

Fig. 11 shows a display picture plane 900 of a PC  
which is obtained by image management list display  
software.

25 The display picture plane 900 comprises a window  
901 and a window 902.

The window 901 is called a tree view. A folder

construction in a hard disk of the PC is shown in the window 901.

When the user designates, for example, a folder shown by "901a" by clicking a mouse from the folder construction shown by the window 901, a list of reduced  
5 images (hereinafter, also referred to as "thumbnail images) 903(1), 903(2), 903(3), ... of image files existing in such a folder is displayed in the window 902 on the right side of the window 901 (hereinafter,  
10 the operation for displaying such thumbnail images is also referred to as a "thumbnail display").

The user, therefore, can easily recognize what kind of images the image files existing in the folder 901a are, or the like without performing the operation  
15 for opening the image files existing in the folder 901a one by one and can easily find a desired image.

Each of the thumbnail images 903(1), 903(2), 903(3), ... which are displayed as a list in the window 902 is reduced and generated so as to go in a frame  
20 (hereinafter, also referred to as a "thumbnail frame") of some fixed size while keeping an aspect ratio.

For example, in the case where a frame size is equal to 100 (in the lateral direction) × 100 (in the vertical direction) pixels (dots) and an image (main  
25 image) serving as an original image of the thumbnail image is set to a size of 640 (lateral direction) × 480 (vertical direction) dots, the thumbnail image is

If the main image is an image having a size of 500 (lateral direction)  $\times$  1000 (vertical direction) dots, a thumbnail image of such a main image is generated at a size of 50 (lateral direction)  $\times$  100 (vertical direction) dots.

In such a case, by performing the photography a plurality of number of times and synthesizing a plurality of photograph images thus obtained in the lateral direction on the PC, a laterally-wide scene such as a landscape or the like can be obtained as one photograph image (one wide image, namely, panorama image).

Specifically speaking, for example, in the case  
20 where one photograph image having a size of 640  
(lateral direction) x 480 (vertical direction) dots is  
obtained by photographing once and a plurality of  
relevant photograph images are synthesized in the  
lateral direction, one scene is divisionally  
25 photographed twice in a manner such that the same  
location overlaps by an amount of 50% in each  
photography in this instance. By synthesizing the two

photograph images thus obtained, a panorama image having a size of 960 (lateral direction)  $\times$  480 (vertical direction) dots can be obtained.

In case of synthesizing three photograph images by photographing three times in a manner similar to the case mentioned above, therefore, a panorama image having a size of 1280 (lateral direction)  $\times$  480 (vertical direction) dots is obtained. A panorama image having a size of 1600 (lateral direction)  $\times$  480 (vertical direction) dots is obtained by photographing four times. A panorama image having a size of 1920 (lateral direction)  $\times$  480 (vertical direction) dots is obtained by photographing five times.

In the conventional display apparatus using the image management list display software as mentioned above, however, if the laterally-wide panorama image obtained by synthesizing a plurality of photograph images in the lateral direction is thumbnail displayed, an image like an elongated rod is displayed in a frame.

For example, if it is intended to display a main image 921 of 1920 (lateral direction)  $\times$  480 (vertical direction) dots as shown in Fig. 12A so as to go in a thumbnail frame of 100 (lateral direction)  $\times$  100 (vertical direction) dots as shown in Fig. 12B, a thumbnail image 921' of the panorama image (main image) 921 is generated at a size of 100 (lateral direction)  $\times$  25 (vertical direction) dots and displayed in a state

like an elongated rod.

In the case where a further laterally-wide main  
image of 3840 (lateral direction) × 480 (vertical  
direction) dots (image obtained by photographing 10  
5 times and synthesizing ten photograph images in the  
lateral direction, or the like) is thumbnail displayed,  
a thumbnail image of such a main image is generated at  
a size of 100 (lateral direction) × 13 (vertical  
direction) dots and displayed in a state like a further  
10 elongated rod.

As mentioned above, in the conventional apparatus,  
if the laterally-wide image is thumbnail displayed, it  
is displayed in an elongated state like a rod.  
Therefore, even if the user looks at the thumbnail  
15 displayed image, it is extremely difficult to  
distinguish what kind of image the observed image is.

That is, although it is an object of the image  
management list display software for the user to easily  
identify the image by thumbnail displaying it, if a  
20 number of laterally-wide images exist as main images,  
the object such that the user can identify those images  
cannot be accomplished.

Also in the case where the main image is a  
vertically-long image (image obtained by photographing  
25 a plurality of number of times and synthesizing a  
plurality of photograph images in the vertical  
direction, or the like), if such a main image is

20250423 12:22:00

thumbnail displayed, it is displayed in an elongated state where it is vertically long like a rod.

Therefore, even if the user looks at the thumbnail displayed image, it is extremely difficult to

5 distinguish what kind of image the observed image is.

#### SUMMARY OF THE INVENTION

It is an object of the invention to solve all or at least one of the above problems.

10 Another object of the invention is to provide an image processing apparatus in which even in case of a laterally-wide or vertically-long image, the user can easily and certainly recognize it by a thumbnail display.

15 To accomplish the above object, there is provided an image processing apparatus comprising: image obtaining means for obtaining a second image of a predetermined aspect size ratio from a first image on the basis of an aspect size ratio of the first image;  
20 and reducing means for reducing the second image obtained by the image obtaining means.

There is also provided an image processing apparatus with the above construction, wherein in case of a size out of a predetermined range, the image  
25 obtaining means obtains the second image when the aspect size ratio of the first image is larger than a predetermined value.

There is also provided an image processing apparatus comprising: image obtaining means for obtaining at least two images of a second image of an arbitrary area portion of a first image and a third  
5 image of another area portion on the basis of an aspect size ratio of the first image; and reducing means for reducing the second and third images obtained by the image obtaining means by different reduction ratios.

The above and other objects and features of the  
10 present invention will become apparent from the following detailed description and the appended claims with reference to the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

15 Fig. 1 is a diagram for explaining a construction of a terminal apparatus to which the invention is applied in the first embodiment;

Fig. 2 is a block diagram showing a construction in the terminal apparatus;

20 Fig. 3 is a diagram for explaining an example of a data file which is managed by an image management list display process unit of the terminal apparatus;

Fig. 4 is a flowchart for explaining the whole operation of the image management list display process  
25 unit;

Fig. 5 is a flowchart for explaining a thumbnail generating process which is executed by the image

0074252.12500

management list display process unit;

Fig. 6 is a diagram for explaining an example of a thumbnail image obtained as a result of execution of the thumbnail generating process;

5 Fig. 7 is a diagram for explaining an example of a thumbnail image obtained in the second embodiment;

Fig. 8 is a flowchart for explaining the thumbnail generating process in the second embodiment;

10 Fig. 9 is a diagram for explaining an example of a thumbnail image which is obtained in the third embodiment;

Fig. 10 is a flowchart for explaining the thumbnail generating process in the third embodiment;

15 Fig. 11 is a diagram for explaining an example of a display picture plane according to image management list display software; and

Figs. 12A and 12B are diagrams for explaining a conventional thumbnail generating process.

## 20 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the invention will now be described hereinbelow with reference to the drawings.

[First embodiment]

25 The first embodiment is applied to, for example, a terminal apparatus 100 as shown in Fig. 1. The terminal apparatus 100 comprises a personal computer and is an apparatus having a function such that a

00742432.102200



number of images obtained by external equipment such as scanner, digital camera, or the like are fetched into the apparatus by activating image management list display software and displayed as a list (thumbnail display).

As shown in Fig. 1, the terminal apparatus 100 has a construction such that a display 102 for displaying various data, a mouse 103 serving as a typical pointing device, and a keyboard 105 are connected to an apparatus main body (computer main body) 101.

A mouse button 104 is provided for the mouse 103.

Fig. 2 shows the construction of the terminal apparatus 100 in a software (204, 205) or hardware (209) manner.

As hardware 209, the terminal apparatus 100 has not only the display 102, mouse 103, and keyboard 105 shown in Fig. 1 but also a keyboard interface (I/F) 210, a mouse interface 212, a video interface 213, a hard disk 215, and a device interface 214.

The terminal apparatus 100 is constructed in a manner such that the software (operating system: OS) 205 including an input device management process unit 206, a drawing management process unit 207, and a file process unit 208 can operate on the hardware 209.

Further, the terminal apparatus 100 is constructed in a manner such that the software (application software) 204 including an image management list

09742433.122200

display process unit (process unit by the image management list display software) 201 can operate on the operating system (OS) 205.

5 The keyboard I/F 210 is an interface for enabling the input device management process unit 206 to receive an input from the keyboard 105. The mouse I/F 212 is an interface for enabling the input device management process unit 206 to receive an input from the mouse 103.

10 The video I/F 213 is an interface for enabling the drawing management process unit 207 to draw an image onto the display 102.

15 The hard disk 215 physically stores various files and data. The device I/F 214 is an interface for enabling the file process unit 208 to read and write data from/onto the hard disk 215.

20 The input device management process unit 206 has a function for enabling the application software 204 to receive an input from the user without being conscious of the hardware 209.

The drawing management process unit 207 has a function for enabling the application software 204 to draw various data without being conscious of the hardware 209.

25 The file process unit 208 has a function for enabling the application software 204 to input and output files without being conscious of the hardware

09142432.122200

209.

The image management list display process unit 201  
fetches a number of images obtained by the external  
equipment such as scanner, digital camera, or the like  
5 into the terminal apparatus 100, managing those images,  
and displaying a list of them (thumbnail display).

For simplicity of explanation, although not shown  
in Fig. 2, the hardware 209 also has: a CPU for  
controlling the operation of the whole terminal  
10 apparatus 100; a memory in which processing programs  
for executing the functions of the software 204 and  
205, various data, and the like are stored; and the  
like.

The operating system (OS) 205 also has a memory  
15 management process unit and the like.

Fig. 3 shows an example of a data file 300 which  
is managed by the image management list display process  
unit 201.

As shown in Fig. 3, the data file 300 includes an  
20 index file 301 and a thumbnail file 302. The image  
management list display process unit 201 stores such a  
data file 300 onto the hard disk 215 on a folder unit  
basis and manages.

The index file 301 includes table data comprising:  
25 image file name data 303(1), 303(2), 303(3), ...; and  
pointer data 304(1), 304(2), 304(3), ... corresponding  
to the image file name data 303(1), 303(2), 303(3),

09742432.122200

....

The thumbnail file 302 includes data (thumbnail data) 305(1), 305(2), 305(3), ... of reduced images (thumbnail images) of the images existing in the target folder.

In the index file 301, the image file name data 303(1), 303(2), 303(3), ... is data of names ("IMAGE001.JPG", "IMAGE002.JPG", etc.) of the image files existing in the target folder.

The pointer data 304(1), 304(2), 304(3), ... is pointer data to the thumbnail data (thumbnail image data) 305(1), 305(2), 305(3), ... existing in the thumbnail file 302 corresponding to the image file name data 303(1), 303(2), 303(3), ....

Fig. 4 shows a thumbnail displaying process in the image management list display process unit 201.

Step S400:

When the application software 204 is activated on the operating system (OS) 205, the image management list display process unit 201 first displays a picture plane 900 as shown in Fig. 11 onto the display 102 of the terminal apparatus 100 (step S400).

Step S401:

Subsequently, the user designates a desired folder in the folder construction shown by the window 901 of the picture plane 900 by using the mouse 103 or the like (designation by a clicking operation or the like).

00742432.12200

Designated information is supplied to the image management list display process unit 201 through the mouse I/F 212 and input device management process unit 206.

5       Step S402:

Subsequently, the image management list display process unit 201 detects the folder (designated folder) shown by the designated information from the hard disk 215 and executes each process in steps S402 to S407 with respect to each of all data existing in the designated folder.

That is, first, in step S402, the image management list display process unit 201 discriminates whether the target data in the designated folder is an image file or not.

This discrimination is made on the basis of, for example, information in a header portion of the target data.

If the target data is not the image file as a result of the discrimination in step S402, processes in next steps S403 to S406 are skipped and the processing routine advances to step S407, which will be explained hereinafter.

Step S403:

If it is determined as a result of the discrimination in step S402 that the target data is the image file, the image management list display process

00221-22200

unit 201 refers to the image file name data 303(1),  
303(2), 303(3), ... in the index file 301 shown in Fig.  
3, thereby discriminating whether such an image file  
(target image file) has already been registered in the  
5 index file 301 or not. As a result of the  
discrimination, if the image file has already been  
registered, processes in next steps S404 to S406 are  
skipped and the processing routine advances to step  
S407, which will be explained hereinlater.

10 Step S404:

As a result of the discrimination in step S403,  
since the target image file is the image file which was  
newly added or the like, if it is not registered yet in  
the index file 301, the image management list display  
15 process unit 201 additionally registers the name of the  
target image file into the index file 301.

For example, when the name of the target image  
file is assumed to be "IMAGE00X.JPG", as shown in Fig.  
3, "IMAGE00X.JPG" is added as image file name data  
20 303(X) into the image file name data 303(1), 303(2),  
303(3), ... in the index file 301.

Step S405:

The image management list display process unit 201  
reads out the target image file from the hard disk 215.

25 Specifically speaking, the target image file is  
actually opened and loaded into a memory (not shown).

The image management list display process unit 201

00742432.122200

performs a reducing process to the target image file in the memory so that the target image file goes in the thumbnail frame of a predetermined size, and adds the target image file after completion of the reducing process as thumbnail data into the thumbnail file 302 shown in Fig. 3.

When the target image file is "IMAGE00X.JPG", consequently, as shown in Fig. 3, thumbnail data 305(X) in the target image file is added to the thumbnail data (thumbnail image data) 305(1), 305(2), 305(3), ....

Step S406:

The image management list display process unit 201 additionally registers the pointer data of the thumbnail data added to the thumbnail file 302 in step S406 in correspondence to the image file name data which has additionally been registered in the index file 301 in step S404.

When the target image file is "IMAGE00X.JPG", consequently, as shown in Fig. 3, pointer data 304(X) of the thumbnail data in the target image file is additionally registered to image file name data 303(X) in the index file 301.

Step S407:

The image management list display process unit 201 discriminates whether the execution of each process in steps S402 to S406 has been finished or not with respect to all of the data existing in the designated

00224.22200

folder.

As a result of the discrimination, if the data whose process is not executed yet exists in the designated folder, the processing routine is returned to step S402 in order to execute each process in steps S402 to S406 with respect to the unprocessed data.

Thus, if the execution of each process in steps S402 to S406 is finished with respect to all of the data existing in the designated folder, the processing routine advances to next step S408.

Step S408:

The image management list display process unit 201 examines the image file which does not actually exist in the designated folder although it has been registered in the index file 301.

That is, for example, in the case where the user erased the image file from the designated folder or moved it to another folder or the like, the image file which does not actually exist in the designated folder although it has been registered in the index file 301 is generated. Therefore, the image management list display process unit 201 discriminates whether the image file corresponding to it exists or not. If it exists, the data corresponding to the relevant image file is deleted from the index file 301 and thumbnail file 302.

Thus, the thumbnail data for all of the image

00742432.122200



files in the designated folder exist in the thumbnail file 302.

Step S409:

5       The image management list display process unit 201 displays a list of the thumbnail data in the thumbnail file 302 onto the window 902 in the picture plane 900 displayed by the display 102 through the drawing management process unit 207 and video I/F 213.

10       Although the image files existing in the folder designated by the user are thumbnail displayed as mentioned above, in the embodiment, particularly, the generating process of the thumbnail data in step S405 is executed, for example, in accordance with a flowchart shown in Fig. 5.

15       Step S501:

      First, the image management list display process unit 201 opens the target image file and loads it into the memory.

20       For example, it is now assumed that an image 601 as shown in Fig. 6 has been loaded into the memory.

      Step S502:

      The image management list display process unit 201 discriminates whether an aspect ratio of the image 601 is larger than a predetermined value or not.

25       For example, whether a lateral size of the image 601 is larger than a value that is five or more times as large as a vertical size or not or whether the

vertical size is larger than a value that is five or more times as large as the lateral size or not is discriminated.

In the embodiment, although the range where one of the vertical and lateral sizes is the value that is five times as large as the other one has been set, naturally, the invention is not limited to it but it can be freely set at the designing stage. Those sizes can be also set to desired values by the user.

In this case, they can be arbitrarily set to values such that if the user reduces them normally, he will feel it difficult to confirm a thumbnail image.

As a result of the discrimination, if the ratio of the lateral size X and vertical size Y of the image 601 is not larger than 5 : 1, the process in next step S503 is skipped and the processing routine advances to step S504, which will be explained hereinlater.

Step S503:

As a result of the discrimination in step S502, if the ratio of the lateral size X and vertical size Y of the image 601 is larger than 5 : 1, as shown in Fig. 6, the image management list display process unit 201 picks out the image in which the ratio of the lateral size X and vertical size Y is equal to 5 : 1 (in case of a laterally-wide image, the image in which the lateral size X(1) : vertical size Y = 5 : 1; in case of a vertically-long image, the image in which the lateral



Thus, in the case where the thumbnail frame 602 has a size of, for example, 100 dots in the lateral direction  $\times$  100 dots in the vertical direction, a

Step S505:

As mentioned above, according to the embodiment, when a list of the images in the folder designated by the user is displayed (thumbnail display) by the thumbnail image (reduced image), if the aspect ratio of the target image is larger than the predetermined value, the image whose aspect ratio is equal to the predetermined value is obtained from the mid section of

[Second embodiment]

In the embodiment, as shown in Fig. 7, when the

aspect ratio of the target image 601 is out of a predetermined range, an image 601(2) whose aspect ratio lies within a predetermined range is obtained from the mid section of the target image 601. A thumbnail image is generated while keeping the aspect ratio of the image 601(2) and a list is displayed.

At this time, marks 610 are added to the thumbnail image and the resultant image is displayed.

Therefore, in the embodiment, the generating process of the thumbnail data in step S405 shown in Fig. 4 is replaced by a process according to, for example, a flowchart shown in Fig. 8.

Steps S701, S702:

First, in a manner similar to steps S501 and S502 in Fig. 5, the image management list display process unit 201 opens the target image file 601, loads it into the memory (step S701), and discriminates whether the aspect ratio of the image 601 lies within a predetermined range or not (step S702).

For example, whether the ratio of the lateral size X and vertical size Y of the image 601 is equal to or larger than 5 : 1 or not is discriminated. That is, whether the lateral size is equal to a size that is five or more times as large as the vertical size or not or whether the vertical size is equal to a size that is five or more times as large as the lateral size or not is discriminated.

Step S703:

As a result of the discrimination in step S702, if the ratio of the lateral size X and vertical size Y of the image 601 is equal to or larger than 5 : 1, the image management list display process unit 201 generates an image (lateral size X(1) : vertical size Y = 4 : 1) in which the ratio of the lateral size X and vertical size Y is equal to or less than a predetermined value (5 : 1), for example, 4 : 1 from the mid section of the image 601 as shown in Fig. 7.

Thus, in the case where the image 601 is an image of the lateral size X = 1800 dots and the vertical size Y = 200 dots, the image 601(2) (the image of the lateral size X(2) = 800 dots, the vertical size Y = 200 dots) in an area corresponding to 800 dots from the 501st dot in the lateral direction is generated.

Step S704:

The image management list display process unit 201 performs the reducing process to the image 601(2) generated in step S703 so that the image 601(2) goes in an area obtained by excluding an area corresponding to the marks 610 from the thumbnail frame 602 of a predetermined size, thereby generating the thumbnail image of the image 601(2).

At this time, the reducing process is performed while keeping the aspect ratio of the image 601(2) (reducing process at the same zoom ratio in both of the

vertical and lateral directions).

For example, in the case where the thumbnail frame 602 has a size of 100 dots in the lateral direction  $\times$  100 dots in the vertical direction and each of the right and left sides which are necessary for adding the marks 610 has a size of 10 dots in the lateral direction  $\times$  100 dots in the vertical direction, a thumbnail image of 80 dots in the lateral direction  $\times$  20 dots in the vertical direction is generated.

Step S706:

The image management list display process unit 201 adds the marks 610 to both right and left end sections of the thumbnail image of the image 601(2) generated in step S704.

The marks 610 here are, for example, marks of three straight lines in the vertical direction.

Thus, a thumbnail image of 100 dots in the lateral direction  $\times$  20 dots in the vertical direction in which the mark 610 of 10 dots in the lateral direction has been added to each of both of the right and left end sections is generated.

After that, the processing routine advances to step S707, which will be explained hereinafter.

Step S705:

As a result of the discrimination in step S702, if the ratio of the lateral size X and vertical size Y of the image 601 is less than 5 : 1, the image management

00742432.122200

list display process unit 201 performs the reducing process to the image 601 itself so as to go in the thumbnail frame 602 of the predetermined size, thereby generating a thumbnail image of the image 601.

At this time, the reducing process is performed while keeping the aspect ratio of the image 601 (the reducing process at the same zoom ratio in both of the vertical and lateral directions).

Thus, for example, if the thumbnail frame 602 has a size of 100 dots in the lateral direction  $\times$  100 dots in the vertical direction, a thumbnail image of 100 dots in the lateral direction  $\times$  20 dots in the vertical direction is generated.

After that, the processing routine advances to next step S707.

Step S707:

The image management list display process unit 201 adds the thumbnail image generated in step S706 or S705 as thumbnail data into the thumbnail file 302.

As mentioned above, according to the embodiment, when a list of the images in the folder designated by the user is displayed (thumbnail display) by thumbnail images (reduced images), when the aspect ratio of the target image is equal to or larger than the predetermined value, the image whose aspect ratio is less than the predetermined value (value of the aspect ratio which is obtained in consideration of the area



that is necessary for adding the marks) is obtained from the mid section of the target image. The thumbnail image is generated while keeping the aspect ratio of such an image. After that, the marks are  
5 added to both of the right and left end sections of the thumbnail image and the list is displayed. Therefore, a situation such that when the laterally-wide image is thumbnail displayed, it is displayed in an elongated state like a rod as in the conventional one is  
10 eliminated. The user looks at the thumbnail displayed image and can identify what kind of image such an image is. Further, the user can also easily identify that such an image is a laterally-wide image whose aspect ratio is out of the predetermined range.

15 [Third embodiment]

In the embodiment, as shown in Fig. 9, when the slender ratio of the target image 601 is equal to or larger than a predetermined value, an image 601(3) whose aspect ratio is less than the predetermined value  
20 is obtained from the target image 601. Images 601R(3) and 601L(3) at both right and left ends of the image 601(3) are obtained.

The image 601(3) and images 601R(3) and 601L(3) are reduced at different reduction ratios. The reduced  
25 image of the image 601(3) and the reduced images of the images 601R(3) and 601L(3) are synthesized and a resultant image is list displayed as a thumbnail image

of the target image 601.

Therefore, according to the embodiment, the generating process of the thumbnail data in step S405 shown in Fig. 4 is replaced by a process according to, for example, a flowchart shown in Fig. 10.

Steps S801, S802:

First, in a manner similar to steps S501 and S502 in Fig. 5, the image management list display process unit 201 opens the target image file 601, loads it into the memory (step S801), and discriminates whether the aspect ratio of the image 601 is equal to or larger than a predetermined value or not (step S802).

For example, whether the ratio of the lateral size X and vertical size Y of the image 601 is equal to or larger than 5 : 1 or not is discriminated. That is, whether the lateral size is equal to a value that is five or more times as large as the vertical size or not or whether the vertical size is equal to a value that is five or more times as large as the lateral size or not is discriminated.

Step S803:

As a result of the discrimination in step S802, when the ratio of the lateral size X and vertical size Y of the image 601 is equal to or larger than 5 : 1, as shown in Fig. 9, the image management list display process unit 201 generates an image (lateral size X(1) : vertical size Y = 3 : 1) in which the ratio of the

lateral size X and vertical size Y is less than the predetermined value (5 : 1), for example, 3 : 1 from the mid section of the image 601.

Thus, when the image 601 is an image of the  
5 lateral size X = 1800 dots and the vertical size Y = 200 dots, the image 601(3) (the image of the lateral size X(3) = 600 dots, vertical size Y = 200 dots) in an area corresponding to 600 dots from the lateral 601st dot is generated.

10 Step S804:

The image management list display process unit 201 performs the reducing process to the image 601(3) generated in step S803 so that the image 601(3) goes in an area obtained by excluding the areas of the reduced  
15 images of the images 601R(3) and 601L(3) which are obtained in step S809, which will be explained hereinlater, from the thumbnail frame 602 of a predetermined size, thereby generating a reduced image of the image 601(3).

20 At this time, the reducing process is performed while keeping the aspect ratio of the image 601(3) (the reducing process at the same zoom ratio in both of the vertical and lateral directions).

For example, if the thumbnail frame 602 has a size  
25 of lateral 100 dots x vertical 100 dots and each of the reduced images of the images 601R(3) and 601L(3) has a size of lateral 20 dots x vertical 20 dots, a reduced

00742432.122200

image of the image 601(3) of lateral 60 dots  $\times$  vertical 20 dots is generated.

Step S806:

5 The image management list display process unit 201 obtains an image 601L(X) at the left end in the images at both right and left ends obtained by excluding the image 601(3) generated in step S803 from the target image 601.

10 Thus, in the case where the image 601 is an image of the lateral size  $X = 1800$  dots and the vertical size  $Y = 200$  dots and the image 601(3) generated in step S803 is an image of an area corresponding to 600 dots from the lateral 601st dot (the image of the lateral size  $X(3) = 600$  dots and the vertical size  $Y = 200$  dots), the image 601L(X) of the lateral size = 600 dots and the vertical size = 200 dots of 600 dots in a range from the lateral first dot to the 600th dot is obtained.

Step S807:

20 The image management list display process unit 201 performs the reducing process to the image 601L(3) obtained in step S806 so as to go in an area of the reduced image of the image 601L(3) in step S804, thereby generating a reduced image of the image 25 601L(3).

Thus, if the thumbnail frame 602 has a size of lateral 100 dots  $\times$  vertical 100 dots and the reduced

09742432.122200

image of the image 601(3) is an image of lateral 60 dots  $\times$  vertical 20 dots, a reduced image of the image 601L(3) of lateral 20 dots  $\times$  vertical 20 dots is obtained.

5       Step S808:

          The image management list display process unit 201 obtains an image 601R(X) at the right end in the images at both right and left ends obtained by excluding the image 601(3) generated in step S803 from the target  
10   image 601.

          Thus, in the case where the image 601 is an image of the lateral size  $X = 1800$  dots and the vertical size  $Y = 200$  dots and the image 601(3) generated in step S803 is an image of the area corresponding to 600 dots  
15   from the lateral 601st dot (the image of the lateral size  $X(3) = 600$  dots and the vertical size  $Y = 200$  dots), the image 601R(X) of the lateral size = 600 dots and the vertical size = 200 dots of 600 dots in a range from the lateral 1201st dot to the 1800th dot is  
20   obtained.

          Step S809:

          The image management list display process unit 201 performs the reducing process to the image 601R(3) obtained in step S808 so as to go in an area of the  
25   reduced image of the image 601R(3) in step S808, thereby generating a reduced image of the image 601R(3).

002221-2342420

Thus, if the thumbnail frame 602 has a size of lateral 100 dots x vertical 100 dots and the reduced image of the image 601(2) is an image of lateral 60 dots x vertical 20 dots, a reduced image of the image 601R(3) of lateral 20 dots x vertical 20 dots is obtained.

The size of each of the reduced images of the images 601R(3) and 601L(3) is determined on the basis of the size of reduced image of the image 601(3) derived in step S804.

That is, the images 601R(3) and 601L(3) are varied and reduced so as to go in the thumbnail frame when each of the reduced images of the images 601R(3) and 601L(3) is added to the reduced image of the image 601(3).

Step S810:

If each of the reduced images of the images 601(3), 601L(3), and 601R(3) in the mid section and both end sections of the target image 601 is obtained by steps S803 to S809, the image management list display process unit 201 synthesizes those reduced images into one image.

Thus, a thumbnail image of the target image 601 of the lateral 100 dots x vertical 20 dots is generated.

After that, the processing routine advances to next step S811.

Step S805:

As a result of the discrimination in step S802, if it is determined that the ratio of the lateral size X and vertical size Y of the image 601 is less than 5 : 1, the image management list display process unit 201 performs a reducing process to the image 601 itself so that the image 601 goes in the thumbnail frame 602 of the predetermined size, thereby generating the thumbnail image of the image 601.

At this time, the reducing process is performed while keeping the aspect ratio of the image 601 (the reducing process at the same zoom ratio in both of the vertical and lateral directions).

For example, thus, if the thumbnail frame 602 has a size of lateral 100 dots × vertical 100 dots, a thumbnail image of the lateral 100 dots × vertical 20 dots is generated.

After that, the processing routine advances to next step S811.

Step S811:

The image management list display process unit 201 adds the thumbnail image generated in step S810 or S805 as thumbnail data into the thumbnail file 302.

As mentioned above, according to the embodiment, when the list of the images in the folder designated by the user is displayed (thumbnail display) by the thumbnail image (reduced image), if the aspect ratio of the target image is equal to or larger than the





one of the vertical and lateral sizes is ten times as large as the other, or the like). This is because if the image is merely picked out in the first embodiment, there is a possibility that the picked-out portion is  
5 too smaller than the whole image.

On the other hand, when a size ratio is not so large, since an atmosphere of the whole image can be recognized even by observing only the picked-up portion, it is not always necessary to apply the form  
10 like an embodiment 3.

It is, therefore, possible to switch the first to third embodiments in accordance with a magnitude of the aspect ratio.

That is, in the case where the aspect ratio lies  
15 within a range from 3 times to 5 times, the first embodiment is applied and, when it is larger than 5 times, the embodiment can be switched to the third embodiment.

Although the first to third embodiments have been  
20 described with respect to the case where the target image is a laterally-wide image, the invention can be also applied to a case where the target image is a vertically-long image.

For example, in this case, it is sufficient to  
25 construct the apparatus in such a manner that the image whose aspect ratio is less than a predetermined value (the value of the aspect ratio which is determined in

002221-2242420

consideration of the area that is necessary for adding the marks) is obtained from the mid section of the target image and a thumbnail image is generated while keeping the aspect ratio of such an image and, after  
5 that, the marks are added to both upper and lower end sections of the thumbnail image, and the image is list displayed.

As another method, it is also possible to construct the apparatus in such a manner that reduced  
10 images of both upper and lower end sections excluding the mid section of the target image (reduced images obtained by reducing at reduction ratios different from a reduction ratio at the time of reducing the image in the mid section) are added to both upper and lower end  
15 sections of the thumbnail image in the mid section of the target image, and a thumbnail image of the target image is obtained and list displayed.

Naturally, the objects of the invention can be also accomplished by a method whereby program codes of  
20 the software for realizing the functions of the host and terminals in each of the first to third embodiments mentioned above are stored in a storage medium, the storage medium is supplied to a system or an apparatus, and a computer (or a CPU or an MPU) of the system or  
25 apparatus reads out the program codes stored in the storage medium and executes a part or all of actual processes on the basis of the read-out program codes.

09742432.122200

In this case, the program codes themselves read out from the storage medium realize the functions of the embodiments mentioned above, and the storage medium in which the program codes have been stored constructs the invention.

As a storage medium for supplying the program codes, it is possible to use an ROM, a floppy disk, a hard disk, an optical disk, a magnetooptic disk, a CD-ROM, a CD-R, a magnetic tape, a non-volatile memory card, or the like.

Naturally, the invention also incorporates not only a case where a computer executes the read-out program codes, so that the functions of the embodiments mentioned above are realized, but also a case where the OS or the like which operates on the computer executes a part or all of the actual processes on the basis of instructions of the program codes and the functions of the embodiments mentioned above are realized by those processes.

Further, the invention also incorporates a case where the program codes read out from the storage medium are written in a memory equipped for a function expanding board inserted in a computer or a function expanding unit connected to a computer and, thereafter, a CPU or the like equipped for the function expanding board or function expanding unit executes a part or all of the actual processes on the basis of instructions of

